

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK TRACTOR TRAILER (TTT) MAP #1

This list should be used in conjunction with the online GIS routing maps.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

	MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
	5	51 FT	112K	25K	50K	60K	60K
	6	51 FT	112K	25K	50K	60K	66K
	6	62 FT	118K	25K	50K	60K	66K
	7	51 FT	122K	25K	40K	60K	66K
	* 7	62 FT	127K	25K	40K	60K	66K
	* 8	68 FT	137K	25K	40K	60K	66K
	9	75 FT	145K	25K	40K	60K	66K
	9	** 90 FT	152K	22K	40K	40K	40K
	10	** 90 FT	162K	22K	40K	50K	50K
SEALED CONTAINER	5	51 FT	95K	25K	44K	66K	66K

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

* 1000 POUNDS MAY BE ADDED FOR EACH ADDITIONAL FOOT OF OUTER BRIDGE UP TO 5,000 POUNDS MAXIMUM.

** MINIMUM 13' 1" REQUIRED BETWEEN GROUPINGS

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK TRACTOR TRAILER (TTT) MAP #2

This list should be used in conjunction with the online GIS routing maps.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
* 6	51 FT	122K	25K	50K	66K	69K
7	55 FT	137K	25K	44K	66K	72K
* 7	62 FT	142K	25K	44K	66K	72K
* 8	68 FT	152K	25K	44K	66K	72K
8	75 FT	160K	25K	44K	66K	72K
9	75 FT	160K	25K	44K	66K	72K

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

* 1000 POUNDS MAY BE ADDED FOR EACH ADDITIONAL FOOT OF OUTER BRIDGE UP TO 5,000 POUNDS MAXIMUM.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK TRACTOR TRAILER (TTT) MAP #3

This list should be used in conjunction with the online GIS routing maps.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
** 9	90 FT	185K	22K	44K	54K	54K
** 9	95 FT	195K	22K	44K	54K	54K
** 10	95 FT	197K	22K	44K	54K	54K
** 11	100 FT	199K	22K	44K	54K	54K

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

** MINIMUM 13' 1" REQUIRED BETWEEN GROUPINGS

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK CRANES (UNDER OWN POWER) MAP #1

This list should be used in conjunction with the online GIS routing maps.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MIN. FT BETWEEN GROUPINGS	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
2	10 FT	10	55K	27.5K	55K	N/A	N/A
3	12 FT	8	66K	22K	44K	N/A	N/A
3	15 FT	10	70K	27.5K	55K	N/A	N/A
4	17 FT	9	88K	22K	44K	44K	N/A
4	18 FT	10	75K	27.5K	55K	55K	N/A

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

AXLE WEIGHTS CANNOT EXCEED 605 LBS. PER INCH OF TIRE WIDTH OR PERMITTED AXLE WEIGHT.

VEHICLES RANGING BETWEEN 80,000 AND 140,000 LBS. WHICH DO NOT MEET THE CONFIGURATIONS SHOWN IN THIS CHART WILL REQUIRE FURTHER REVIEW BY THE DEPARTMENT FOR CONSIDERATION OF PERMIT ISSUANCE.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK CRANES (UNDER OWN POWER) MAP #2

This list should be used in conjunction with the online GIS routing maps.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MIN. FT BETWEEN GROUPINGS	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
4	20 FT	8	95K	25K	50K	50K	N/A
4	21 FT	8	96K	25K	50K	50K	N/A
4	22 FT	8	97K	25K	50K	50K	N/A
4	20 FT	10	85K	27.5K	55K	55K	N/A
4	16 FT	8	88K	22K	44K	66K	N/A

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

AXLE WEIGHTS CANNOT EXCEED 605 LBS. PER INCH OF TIRE WIDTH OR PERMITTED AXLE WEIGHT.

VEHICLES RANGING BETWEEN 80,000 AND 140,000 LBS. WHICH DO NOT MEET THE CONFIGURATIONS SHOWN IN THIS CHART WILL REQUIRE FURTHER REVIEW BY THE DEPARTMENT FOR CONSIDERATION OF PERMIT ISSUANCE.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

TRUCK CRANES (UNDER OWN POWER) MAP #3

This list should be used in conjunction with the online GIS routing maps.

(Minimum 10 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MIN. FT BETWEEN GROUPINGS	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
5	32 FT	8	100K	22K	44K	66K	66K
5	20 FT	8	97K	22K	44K	66K	66K
5	* 25 FT	10	100K	22K	44K	66K	66K
6	30 FT	8	105K	20K	40K	60K	66K
6	31 FT	8	106K	20K	40K	60K	66K
6	30 FT	10	105K	22K	44K	66K	66K
6	51 FT	8	108K	22K	44K	66K	66K
7	35 FT	10	110K	22K	44K	66K	66K
7	** 51 FT	8	118K	22K	44K	66K	66K
8	* 51 FT	8	122K	22K	44K	66K	66K
8	* 40 FT	10	113K	22K	44K	66K	66K
9	51 FT	10	125K	20K	40K	60K	66K

*/**/** 1,000 pounds may be added to gross weight for each additional foot of outer bridge

* 5,000 pounds maximum

** 4,000 pounds maximum

*** 3,000 pounds maximum

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

AXLE WEIGHTS CANNOT EXCEED 605 LBS. PER INCH OF TIRE WIDTH OR PERMITTED AXLE WEIGHT.

VEHICLES RANGING BETWEEN 80,000 AND 140,000 LBS. WHICH DO NOT MEET THE CONFIGURATIONS SHOWN IN THIS CHART WILL REQUIRE FURTHER REVIEW BY THE DEPARTMENT FOR CONSIDERATION OF PERMIT ISSUANCE.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

WRECKER MAP #1

This list should be used in conjunction with the online GIS routing maps.

(Minimum 21 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
5	61 FT	120K	25K	50K	66K	66K
6	61 FT	135K	25K	50K	66K	66K
7	65 FT	140K	25K	50K	66K	66K

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

MAXIMUM 40 M.P.H. WHEN CROSSING NON-RESTRICTED BRIDGES.

MAXIMUM ALLOWED DISTANCE OF TRAVEL IS 100 MILES.

WEIGHT RESTRICTIONS CHART FOR BLANKET PERMIT VEHICLES

WRECKER MAP #2

This list should be used in conjunction with the online GIS routing maps.

(Minimum 21 ft. spacing required between groupings unless otherwise noted)

MIN. # OF AXLES REQ.	MIN. OUTER BRIDGE	MAX. GROSS WEIGHT	MAX 1 AXLE GROUP WEIGHT	MAX 2 AXLE GROUP WEIGHT	MAX 3 AXLE GROUP WEIGHT	MAX 4 (+) AXLE GROUP WEIGHT
5	61 FT	120K	45K	90K	90K	90K
6	61 FT	135K	45K	90K	90K	90K
7	61 FT	140K	45K	90K	90K	90K

“K” REPRESENTS 1,000 POUNDS. Example: 112K = 112,000 Pounds

ONE QUALIFIED ESCORT IS REQUIRED.

NO OTHER TRAFFIC IS ALLOWED ON NON-RESTRICTED BRIDGES WHEN USING WRECKER MAP #2.

ESCORT(S) MUST BE POSITIONED IN THE REAR OF THE LOAD, STRADDLING LANES WHEN CROSSING NON-RESTRICTED BRIDGES ON ROUTE.

MAXIMUM 30 M.P.H. WHEN CROSSING NON-RESTRICTED BRIDGES.

MAXIMUM ALLOWED DISTANCE OF TRAVEL IS 50 MILES.